

Safety data sheet

according to 1907/2006/EC, Article 31

Trade name: : Baustick Thermal Insulation Silicone Based Paint (BS - 025)

- **1 Identification of the substance/mixture and of the company/undertaking**

- **Product identifier**
- **Trade name: Baustick Thermal Insulation BS - 025 Silicone Based Paint**
- **Relevant identified uses of the substance or mixture and uses advised against**
- **Application of the substance / the preparation: Water Based Paint**
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Baustick Boya ve Yapı Kimyasalları San. ve Tic. Ltd. Şti.
Yakuplu Mah. Hurriyet Bul. 35. Sk. No 20/B.
Beylikdüzü / İstanbul.
- **Tel :** + 90 212 876 46 96 Mail. info@baustick.com
- **Fax:** + 90 212 876 72 43
- **Emergency telephone number:** 00 90 212 876 46 96

- **2 Hazards identification**

- **Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
GHS07 exclamation mark
Skin Sens. 1 H317 May cause an allergic skin reaction.
- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**
Xi; Sensitizing.
R43: May cause sensitisation by skin contact.
- **Information concerning particular hazards for human and environment:**
The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
- **Classification system:**
The classification is according to the latest editions of the EU-lists, and extended by company and literature data.
- **Label elements**
- **Labelling according to EU guidelines:**
The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.
- **Code letter and hazard designation of product:**
Xi Irritant
- **Hazard-determining components of labelling:**
mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2-Isothiazol-3-one [EC no. 220-239-6] (3:1) mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-4-isothiazolin-3-one [EC no. 220-239-6] (3:1)
- **Risk phrases:**
43 May cause sensitization by skin contact.

Safety data sheet

according to 1907/2006/EC, Article 31

Trade name: : Baustick Thermal Insulation Silicone Based Paint (BS - 025)

- **Safety phrases:**
 - 2 Keep out of the reach of children.
 - 23 Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).
 - 24/25 Avoid contact with skin and eyes.
 - 37 Wear suitable gloves.
 - 46 If swallowed, seek medical advice immediately and show this container or label.
 - 56 Dispose of this material and its container to hazardous or special waste collection point.
- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

- **3 Composition/information on ingredients**

- **Chemical characterization: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

- Dangerous components:		
CAS: 12001-26-2	Mica	2.5-10%
CAS: 1332-58-7	Kaolin	2.5-10%
CAS: 64742-88-7 EINECS: 265-191-7	Solvent naphtha (petroleum), medium aliph. Xn R65 GHS08 Asp. Tox. 1, H304	≤ 2.5%
CAS: 55965-84-9	mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-4-isothiazolin-3-one [EC no. 220-239-6] (3:1) T R23/24/25; C R34; Xi R43; N R50/53 GHS06 Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; GHS05 Skin Corr. 1B, H314; GHS09 Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1, H317	≤ 2.5%

Additional information: For the wording of the listed risk phrases refer to section 16.

- **4 First aid measures**

- **Description of first aid measures**
- **After inhalation:**
 - Supply fresh air and to be sure call for a doctor.
 - In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.

Safety data sheet

according to 1907/2006/EC, Article 31

Trade name: : Baustick Thermal Insulation Silicone Based Paint (BS - 025)

- **5 Firefighting measures**

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

- **6 Accidental release measures**

- **Personal precautions, protective equipment and emergency procedures:** Not required.
- **Environmental precautions:** Dilute with plenty of water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
- **Reference to other sections:**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

- **7 Handling and storage**

- **Handling:**
- **Precautions for safe handling:**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols
- **Information about fire - and explosion protection:**
No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** None.

- **8 Exposure controls/personal protection**

- **Additional information about design of technical facilities:** No further data; see item 7.
- **Control parameters**

Ingredients with limit values that require monitoring at the workplace:

1332-58-7 Kaolin

WEL	Long-term value: 2 mg/m ³
-----	--------------------------------------

12001-26-2 Mica

WEL	Long-term value: 10* 0.8** mg/m ³ *total inhalable **respirable
-----	---

- **Additional information:** The lists valid during the making were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.

Safety data sheet

according to 1907/2006/EC, Article 31

Trade name: : Baustick Thermal Insulation Silicone Based Paint (BS - 025)

- **Respiratory protection:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:** Goggles recommended during refilling

- **9 Physical and chemical properties**

- Information on basic physical and chemical properties	
- General Information	
- Appearance:	
- Form: Fluid	
- Colour:	According to product specification
- Odour: Characteristic	
- pH-value at 20°C:	7-9
- Change in condition	
- Meltingpoint/Melting range:	Undetermined.
- Boilingpoint/Boiling range:	100 °C
- Flash point:	Not applicable
- Self-igniting:	Product is not selfigniting.
-	
- Danger of explosion:	Product does not present an explosion hazard.
- Vapour pressure at 20°C:	23 hPa
- Density at 20°C:	1.52-1.58 g/cm ³
- Solubility in / Miscibility with water:	Fully miscible.
- Solvent content:	
- Solids content:	69.0 %

Safety data sheet

according to 1907/2006/EC, Article 31

Trade name: : Baustick Thermal Insulation Silicone Based Paint (BS - 025)

- **10 Stability and reactivity**

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition /conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions:** No dangerous reactions known.
- **Hazardous decomposition products:** No dangerous decomposition products known.

- **11 Toxicological information**

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Irritant
- **Sensitisation:** May cause sensitisation by skin contact.

- **12 Ecological information**

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Generally not hazardous for water
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

- **13 Disposal considerations**

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Un cleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

- **14 Transport information**

- **Land transport ADR/RID (cross-border)**
- **ADR/RID class:** -
- **Maritime transport IMDG:**
- **IMDG Class:** -
- **Marine pollutant:** No
- **Air transport ICAO-TIandIATA-DGR:**

Safety data sheet

according to 1907/2006/EC, Article 31

Trade name: : Baustick Thermal Insulation Silicone Based Paint (BS - 025)

- **ICAO/IATA Class:** -
- **UN "Model Regulation ":** -
- **Special precautions for user :** Not applicable.
- **Transport/Additional information:**
This product is not classified as dangerous according to the transportation rules.

- **15 Regulatory information**

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **National regulations:**

Class	Share in %
Water	26.4
NK	1,4

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

- **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

H301 Toxic if swallowed.
H304 May be fatal if swallowed and enters airways.
H311 Toxic in contact with skin.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H331 Toxic if inhaled.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
R23/24/25 Toxic by inhalation, in contact with skin and if swallowed.
R34 Causes burns.
R43 May cause sensitisation by skin contact.
R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65 Harmful: may cause lung damage if swallowed.

- **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO: International Civil Aviation Organization
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)
GHS: Globally Harmonized System of Classification and Labelling of Chemicals

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.